

RE-716P1TLP(Y)

MANUAL ABORT STATION – DUAL ACTION

General

Manual Abort Station is made up of a high quality non-toxic die-cast material. Low profile design and smooth edges offer an attractive yet functional design. All components are pre-painted or have plated surfaces to inhibit corrosion. Electrically the manual abort station is unbeatable with 10 Amp snap action switch offered in all possible contact arrangements (including gold contacts). The manual abort station can be used with or without a break glass rod with replacement requiring no special tools. ABORT embossed on the enclosure for easy visibility and non removable during tear and wear.



Features

- UL Listed.
- Break glass Rod.
- Weather and Explosion proof versions (Optional).
- All stations offer hex screw or key lock access.
- Yellow colour.
- ABORT Written on top for easy Visibility.
- Dual Action Lift and Pull.
- Easy to Install.

Construction Material

- Painted Die Cast Housing.
- 14 Ga plated steel black plate.
- Corrosion inhibited surfaces.
- Terminal block (2 Position).
- Single Gang Mounting
- 10 A, 120VAC snap action switch (S.P.S.T.)

Specification

Electrical Specification

Switch SPST 10A@120VAC

Mechanical Specification

Dimension (3.200W x 4.750L x 0.875D) inches

Weight 15.5 oz / 420 grams

Mount Single gang

Compatible Panel

Model	Description
RE-120GR	Conventional Gas Release Control Panel
RE-25AR	Conventional Agent Release Control Panel

Ordering Information

Model	Description
RE-716P1TLP(Y)	Manual Abort Station Dual Action - Yellow

India

RAVEL ELECTRONICS PVT LTD.,
150A, Electronics Industrial Estate,
Perungudi, Chennai – 96, India.
E-mail: marketing@ravelfire.com; Web: www.ravelfire.com

United Kingdom

RAVEL ELECTRONICS LTD.,
Unit 11, Chancel Industrial Estate, Newhall street,
Willenhall WV13 1NX, West Midlands, United Kingdom.
E-mail: info@ravelfire.co.uk; Web: www.ravelfire.co.uk

USA

RAVEL AMERICAS INC.,
2855 NW 112th Ave ST#2 Miami,
Doral, Florida 33172, USA.